Sanjay Ghodawat University, Kolhapur

2020-21

Established as State Private University under Govt. of Maharashtra. Act No XL, 2017

EXM/P/09/00

Year and Program: T.Y.B.Tech	**School of Technology**	**Department: Civil**
Course Code: CET 301 R1	**Course Title: Design of RCC Structures**	**Semester : V**
Day : Monday **Date: 14.12.2020**	**End Semester Examination**	**Time:2 Hrs.** **Max Marks:50**

Instructions: 1) All Questions are compulsory.
2) Assume suitable data wherever necessary.

		Marks	Bloom's Level	CO
Q.1	**Answer the following (Any Two)**–			
a)	A rectangular beam 230 mm wide and 415 mm deep upto the center of reinforcement have to resist a Bending moment of 25 kNm at working condition. Calculate the reinforcement required if M20 and Fe 415 are used	8	L_3	CO1
b)	Calculate the moment of resistance of doubly reinforced rectangular beam for the following data, width of beam = 300 mm, overall depth = 450 mm, steel on compression side = 3 bars of 22mm + 2 bars of16mm, steel on tension side = 6 bars of 20mm, Take effective cover for each reinforcement = 35 mm. Use M15 and Fe250.	8	L_3	CO1
c)	RC beam 350 mm wide and 550 mm deep is reinforced with 4 numbers of 25 mm bars on tension side with an effective cover of 50 mm. Design the shear reinforcement needed for a factored shear force of 275 kN. Concrete M20 and mild steel.	8	L_6	CO2
Q.2	**Answer the following (Any two)** –			
a)	Design simply supported one way slab from following data, Effective span 3.83m, live load = 3kN/m^2, floor finish = 0.5 kN/m^2. Use M20 and Fe 415.	8	L_6	CO2
b)	Design of two way slab over a room 5m X 7m. The edges of the slab are simply supported and corners are not held down (not restrained). The live load on the slab is 2.75kN/m^2. The slab has bearing of 300mm on the supporting wall. Use M15 Concrete and Fe 415 steel.	8	L_6	CO3

c)	Design the section and steel for an axially loaded column, for an ultimate axial load of 2100 kN with an effective length of 2.75 m. use M20 grade concrete Fe 415 steel	8	L_6	CO3

Q.3 Answer the following (Any two) –

a)	Design a square isolated pad footing to carry a column load of 1250kN, S.B.C. of soil is 100kN/m^2, unit weight of soil 20 kN/m^3, load factor as 1.5. Use M15 and Fe415.	9	L_4	CO4
b)	Design an isolated rectangular footing with constant depth for the column size 230 mm X 650 mm carrying an axial load of 1200 kN. The S.B.C. of soil is 300 kN/m^2. Use M20 and Fe415.	9	L_4	CO4
c)	Discuss the advantages and disadvantages of prestressed concrete over Reinforced cement concrete	9	L_2	CO4

*****